

SPEEDFOX AL ONE



Frame	Speedfox Premium Aluminium with APS Suspension System with 120 mm <ul style="list-style-type: none"> • Internal cable routing • BSA threaded bottom bracket • Post mount disc • 12x148 mm boost thru-axle
Fork	Rock Shox Recon Silver RL 130 mm
Seatpost	X-Fusion Manic Dropper 125/150 mm, 31.6 mm
Shock	Fox Float DPS, Performance, Evol
Handlebar	BMC MRB03 Alloy 760 mm
Stem	BMC AMSM02
Saddle	WTB Silverado Comp
Gears	1x12
Crankset	SRAM Stylo 6k Eagle 30T
Cassette	SRAM NX Eagle 11-50T
Chain	SRAM NX Eagle

Front Derailleur	-
Rear Derailleur	SRAM NX Eagle
Shifters	SRAM NX Eagle
Brakes	Shimano Deore / Shimano SM-RT54 Rotors (180/180)
Rims	Alex MD30, 30 mm
Hubs (F/R)	Shimano HB-MT400-B / FH-MT400-B
Tires	Maxxis Forekaster 29x2.35 TR, EXO
Sizes	S, M, L, XL
Colour	Sand
Weight	14.65 kg
Tire Clearance	58 mm
ASTM Classification	Level 4
Weight Limit	120 kg
Additional Equipment	Tubeless Ready (Rim Strip & Valves Included)

Size	SKU TW
S	30000438
M	30000439
L	30000440
XL	30000441